


## **Product Specification Sheet**

## NRS S 2W 39x20 w/Wipers

## Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NRS S 2W 39x20 w/Wipers today!







Nominal Rod Diameter [mm]     39       Details     20       End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]     35       Dimensions     35       D1 [mm]     80       D7 [mm]     7       D8 [mm]     50       L1 [mm]     110       L2 [mm]     126       Keyway (L x b x h)     40x8x3	Product Info	
Details     20       End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]     35       Dimensions     80       D1 [mm]     7       D8 [mm]     50       L1 [mm]     110       L2 [mm]     126       Keyway (L x b x h)     40x8x3		39
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]   35     Dimensions   80     D1 [mm]   7     D8 [mm]   50     L1 [mm]   110     L2 [mm]   126     Keyway (L x b x h)   40x8x3		
Dimensions     80       D1 [mm]     7       D7 [mm]     7       D8 [mm]     50       L1 [mm]     110       L2 [mm]     126       Keyway (L x b x h)     40x8x3	Lead [mm]	20
Dimensions     80       D1 [mm]     80       D7 [mm]     7       D8 [mm]     50       L1 [mm]     110       L2 [mm]     126       Keyway (L x b x h)     40x8x3	End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	35
D7 [mm]   7     D8 [mm]   50     L1 [mm]   110     L2 [mm]   126     Keyway (L x b x h)   40x8x3		
D8 [mm]   50     L1 [mm]   110     L2 [mm]   126     Keyway (L x b x h)   40x8x3	D1 [mm]	80
L1 [mm] 110   L2 [mm] 126   Keyway (L x b x h) 40x8x3	D7 [mm]	7
L2 [mm]     126       Keyway (L x b x h)     40x8x3	D8 [mm]	50
Keyway (L x b x h) 40x8x3	L1 [mm]	110
	L2 [mm]	126
Performance Specifications	Keyway (L x b x h)	40x8x3
	Performance Specifications	
Dynamic Load Ratings Ca [kN] 86.70		86.70
Static Load Ratings Coa [kN] 109.20	Static Load Ratings Coa [kN]	109.20