


## PowerTrac 1250 - 0500 SGT RA, with SSN Ball Nut, Preloaded,

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerTrac 1250 - 0500 SGT RA, with SSN Ball Nut,







Inch Ball Screw	
(Screw)Product Info	
Screw Code	1250-0500 SGT RA
Precision	SGT
Screw Material	4150
Thread Direction	RH
(Screw)Details	4.050
Ball Circle Diameter [in]	1.250
Lead [in]	0.500
Root Diameter [in]	1.050
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	25
End Code for Type 4 [* Journals may show tracings of the thread]	16
(Screw)Performance Specifications	
Lead Accuracy +/- [in./ft.]	0.0005
(Screw)Part Numbers	
2 ft. Part Number	
4 ft. Part Number	
6 ft. Part Number	GT12550R72
8 ft. Part Number	
12 ft. Part Number	
16 ft. Part Number	
20 ft. Part Number	
(Screw)Weight	
Screw Weight [lb./ft.]	3.70
Inch Ball Nut, for SGT and XPR, Ground Accuracy, Preloaded, Fixed, SSN	0.10
(Nut)Product Info	
Ball Nut Number	SSN0399
Thread Direction	RH
(Nut)Details	TWI
Ball Circle Diameter [in]	1.250
Lead [in]	0.500
Nominal Ball Diameter [in]	0.188
Root diameter [in]	1.050
	1.050
(Nut)Forces and Torques	0.000
Torque to Raise 1 lb. [in-lb]	0.088
(Nut)Flange Part Numbers	INITEODAL
Flange Part Number	INTEGRAL
(Nut)Wiper Part Numbers	FLACTOMED
Wiper Kit Part Number	ELASTOMER
(Nut)Weight	
Nut Weight [lb]	3.20
(Nut)Performance Specifications	
Maximum Adjustable Preload [lb]	
Spring Rate x 10 <sup>6</sup> [lb./in.]	4.25
Dynamic Load [lb]	1765
Static Load [lb]	11080