


PowerTrac 3000 - 0660 SRT LA, with SBN Ball Nut, Triple Circuit

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerTrac 3000 - 0660 SRT LA, with SBN Ball Nut, Triple



Inch Ball Screw

(Screw)Product Info

Screw Code	3000-0600 SRT LA
Precision	SRT
Screw Material	4150
Thread Direction	LH

(Screw)Details

Ball Circle Diameter [in]	3.000
Lead [in]	0.660
Root Diameter [in]	2.480
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	60
End Code for Type 4 [* Journals may show tracings of the thread]	39

(Screw)Performance Specifications

Lead Accuracy +/- [in./ft.]	0.0080
-----------------------------	--------

(Screw)Part Numbers

2 ft. Part Number	
4 ft. Part Number	SRT0410
6 ft. Part Number	
8 ft. Part Number	SRT0411
12 ft. Part Number	SRT0412
16 ft. Part Number	SRT0413
20 ft. Part Number	SRT0414

(Screw)Weight

Screw Weight [lb./ft.]	19.60
------------------------	-------

Inch Ball Nut, for SRT, Standard Accuracy, No Preload, SBN, Standard

(Nut)Product Info

Ball Nut Number	SBN10257
Thread Direction	LH

(Nut)Details

Ball Circle Diameter [in]	3.000
Lead [in]	0.660
Nominal Ball Diameter [in]	0.500
Root diameter [in]	2.480

(Nut)Dimensions

A [in]

(Nut)Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.117
-------------------------------	-------

(Nut)Flange Part Numbers

Flange Part Number	FLG7575
--------------------	---------

(Nut)Wiper Part Numbers

Wiper Kit Part Number	WKB2661
Wiper Kit Felt Part Number	

(Nut)Weight

Nut Weight [lb]	26.00
-----------------	-------

(Nut)Performance Specifications

Lead Accuracy +/- [in./ft.]	0.008
Maximum Adjustable Preload [lb]	
Spring Rate x 10 ⁶ [lb./in.]	
Dynamic Load [lb]	44316
Static Load [lb]	271733