




MBN20x20R-4FW

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your MBN20x20R-4FW today!



Lube hole can be on either side of nut depending on size.
See table below for lube hole location.

Product Info

Nominal Rod Diameter [mm]	20
Material	Alloy
Thread Direction	RH

Details

Lead [mm]	20
Active Turns	4
Nominal Ball Dia. [mm]	3.500
Screw Weight [kg/m]	1.94
Nut Weight [kg]	0.24
Lube Hole Location	L
End Code for Types 1,2, and 3	15
End Code for Types 4	10
End Code for Types 5	15
End Code for Types 6	15
End Code for Types 7	15

Performance Specifications

Dynamic Load Ca [N]	12110
Static Load [N]	22010
Linear Speed (Based on DN Values) [mm/min]	70000

Screw Dimensions

d0 [mm]	20
d1 [mm]	19.26
d2 [mm]	16.38

Nut Dimensions

D1 (g6) [mm]	36
L [mm]	36
L1 [mm]	10
Lx [mm]	35
Lz [mm]	5
L3 (min) [mm]	4
L7 [mm]	10
L8 [mm]	44
D4 [mm]	47
D5 [mm]	6 × 6.6
D6 [mm]	58