


NMR 15ML ZU Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NMR 15ML ZU Assembly today!



| | |
|---|----------|
| Dimensions | |
| H [mm] | 16 |
| W2 [mm] | 8.5 |
| Standard Miniature Block Four Mounting Holes (Runner Block)Details | |
| Size [mm] | 15 |
| (Runner Block)Dimensions | |
| W [mm] | 32 |
| L [mm] | 60 |
| L1 [mm] | 44 |
| h2 [mm] | 12.3 |
| P1 [mm] | 25 |
| P2 [mm] | 25 |
| M × g2 | M3 × 5.5 |
| Ø [mm] | 1.8 |
| S [mm] | 3.3 |
| T [mm] | 4.3 |
| (Runner Block)Forces and Torques | |
| Basic Load Ratings C [N] | 5350 |
| Basic Load Ratings C0 [N] | 9080 |
| Static Moment Ratings-Ma [N-m] | 63.3 |
| Static Moment Ratings-Mb [N-m] | 63.3 |
| Static Moment Ratings-Mc [N-m] | 70.0 |
| (Runner Block)Weight | |
| Weight-Block [g] | 90 |
| Standard Miniature Rail Top Mount (Top Mount Rail)Details | |
| Size [mm] | 15 |
| (Top Mount Rail)Dimensions | |
| H [mm] | 16 |
| W1 [mm] | 15 |
| H1 [mm] | 9.5 |
| P [mm] | 40 |
| D [mm] | 6 |
| d1 [mm] | 3.5 |
| g1 [mm] | 4.5 |
| (Top Mount Rail)Weight | |
| Weights-Rail [g/m] | 930.0 |
| Standard Miniature Rail Bottom Tapped Mount (Bottom Mount Rail)Details | |
| Size [mm] | 15 |
| (Bottom Mount Rail)Dimensions | |
| H1 [mm] | 9.5 |
| W1 [mm] | 15 |
| P [mm] | 40 |
| M1 | M4 x 0.7 |
| (Bottom Mount Rail)Weight | |
| Weights-Rail [g/m] | 930.0 |