

# NMR 12ML ZUE Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NMR 12ML ZUE Assembly today!

2D/3D CAD ONLINE






| | |
|---|---|
| **Dimensions** | |
| H [mm] | 13 |
| W2 [mm] | 7.5 |
| **Standard Miniature Block Four Mounting Holes (Runner Block)Details** | |
| Size [mm] | 12 |
| **(Runner Block)Dimensions** | |
| W [mm] | 27 |
| L [mm] | 49 |
| L1 [mm] | 34 |
| h2 [mm] | 10.8 |
| P1 [mm] | 20 |
| P2 [mm] | 20 |
| M × g2 | M3 × 3.5 |
| Ø [mm] | 1.3 |
| S [mm] | 3.2 |
| T [mm] | 4.3 |
| **(Runner Block)Forces and Torques** | |
| Basic Load Ratings C [N] | 3240 |
| Basic Load Ratings C0 [N] | 5630 |
| Static Moment Ratings-Ma [N-m] | 30.2 |
| Static Moment Ratings-Mb [N-m] | 30.2 |
| Static Moment Ratings-Mc [N-m] | 34.9 |
| **(Runner Block)Weight** | |
| Weight-Block [g] | 51 |
| **Standard Miniature Rail Top Mount (Top Mount Rail)Details** | |
| Size [mm] | 12 |
| **(Top Mount Rail)Dimensions** | |
| H [mm] | 13 |
| W1 [mm] | 12 |
| H1 [mm] | 7.5 |
| P [mm] | 25 |
| D [mm] | 6 |
| d1 [mm] | 3.5 |
| g1 [mm] | 4.5 |
| **(Top Mount Rail)Weight** | |
| Weights-Rail [g/m] | 602.0 |
| **Standard Miniature Rail Bottom Tapped Mount (Bottom Mount Rail)Details** | |
| Size [mm] | 12 |
| **(Bottom Mount Rail)Dimensions** | |
| H1 [mm] | 7.5 |
| W1 [mm] | 12 |
| P [mm] | 25 |
| M1 | M4 x 0.7 |
| **(Bottom Mount Rail)Weight** | |
| Weights-Rail [g/m] | 602.0 |